



Description	Technical Data
<p>Table system FB 470 Part no. 116.00051</p> <p>The table system FB 470 is used for Call-Center tables, office desks, speaker desks and elementary assembly tables. It is assembled in just a few minutes.</p>	<ul style="list-style-type: none"> • Lifting capacity max. 80 kg • Lifting length max. 470 mm (675 - 1145 mm) • Speed max. 40 mm/s • Plate breadth: 600 - 800 mm • Plate length: 1200 - 2000 mm • Color: white aluminium RAL 9006 powder coated



Description	Technical Data
<p>Table system FC 650 Art. Nr.: 116.00061</p> <p>The table system FB 470 is used for Call-Center tables, office desks, speaker desks and elementary assembly tables. It is assembled in just a few minutes.</p>	<ul style="list-style-type: none"> • Lifting capacity max. 80 kg • Lifting length max. 650 mm (620 - 1270 mm) • Speed 40 mm/s • Plate breadth: 600 - 800 mm • Plate length: 1200 - 2000 mm • Color: white aluminium RAL 9006 powder coated
<p>Technical drawing showing side and front views of the table system FC 650. Dimensions include: total length 1200 - 2000 mm, lifting length 1100 - 1900 mm, plate length 50 mm, plate thickness 56 mm, lifting height 615 + Hub / Stroke max. 650 mm, leg diameter 60 mm, base width 75 mm, and base height 30 mm.</p>	<p>Technical drawing showing top and front views of the table plate. Dimensions include: plate breadth 600 - 800 mm, plate width 338 mm, plate thickness 20 mm, and base width 630 mm and 725 mm.</p>